

WOODBIDGE

WINDOWS by B.F. Rich

New Construction



STRUCTURAL DATA



Window Type	Test Method	Primary Product Designator	Air Infiltration/ Exfiltration	Water Penetration Resistance	Design Pressure	Tested Pressure (Uniform Load Structural)	Forced Entry Resistance
Woodbridge Double-Hung	AAMA/WDMA/CSA 101/I.S.2/ A440-05	H-R50 40" x 66" (1000mm x 1675mm)	0.14 cfm/ft ² (1.57 psf) (25 mph)	360 pa (7.5 psf)	2400 pa (50 psf)	3590 pa (75.0 psf)	Passed ASTM F588 Grade 10
Woodbridge Horizontal Slider	AAMA/WDMA/CSA 101/I.S.2/ A440-05	HS-R40 66" x 44" (1675mm x 1120mm)	0.12 cfm/ft ² (1.57 psf) (25 mph)	330 pa (6.75 psf)	2160 pa (45 psf)	2880 pa (60.0 psf)	Passed ASTM F588 Grade 10
Woodbridge Fixed Lite	AAMA/WDMA/CSA 101/I.S.2/ A440-05	FW-LC55 56" x 56" (1400mm x 1400mm)	0.01 cfm/ft ² (1.57 psf) (25 mph)	580 pa (12.0 psf)	2880 pa (60 psf)	3960 pa (82.5 psf)	Passed ASTM F588 Grade 10