



Cabernet Elite Green Shield Vinyl Window by BFRich Windows & Doors								
WINDOW TYPE	TEST METHOD / TEST NUMBER	WINDOW SIZE	AIR INFILTRATION @ 15 MPH / @ 25 MPH	WATER PENETRATION (PSF)	STRUCTURAL PERFORMANCE (PSF)	STRUCTURAL GRADE	DESIGN PRESSURE RATING	EQUIVALENT WIND VELOCITY
Elite DH	AAMA/NWWDA 101/ I.S.2/ A440-05 NFRC 110-7310-3	40" x 63"	0.10 0.14	11.25	82.5	H-R55	DP-55	179 MPH
Elite DH	AAMA/NWWDA 101/ I.S. 2-97 NFRC 110-7310-3	Certification Number N10004698 EXTENSION						
Elite HS	AAMA/NWWDA 101/ I.S. 2-97 NFRC 110-7310-4	69" x 48"	0.07 0.16	3.75	67.5	HS-R25	DP25	121 MPH
Elite PW	AAMA/NWWDA 101/ I.S. 2-97 NFRC 110-6330-1	54" x 54"	0.01 0.06	12.00	135	F-LC85	DP-85	216 MPH
Elite CSMT	AAMA/NWWDA 101/ I.S. 2-97 NFRC 110-6174-1	24" x 48"	0.07 0.11	7.50	75	C-LC50	DP50	171 MPH
Elite AWN	AAMA/NWWDA 101/ I.S. 2-97 NFRC 110-7512-1	48" x 29"	0.10 0.11	11.25	82.5	AP-R55	DP55	179 MPH

AAMA (American Architectural Manufacturers Association) has developed specifications to test and rate the performance, quality and reliability of architectural building components. BFRich voluntarily tests our products to AAMA specifications for structural performance, air infiltration, water resistance, operating force and forced entry resistance. The table above briefly outlines the results of these tests and provides the overall structural rating for each product. More detailed performance information, as well as copies of test reports, are available upon request.

Please call our Customer Service Department for any additional information at 1-800-237-4241. Corporate web site: www.bfrich.com